Primero

LUXURY VINYL TILES





Intro

PRIMERO

Luxury Vinyl Tiles (LVT) floors are a popular choice in homes because of the numerous benefits they offer. The durable vinyl planks and tiles consist of different layers, each one offering a specific characteristic. Developed and made in Belgium, Primero comes with the well-known benefits of LVT flooring: comfort, softness and warmth, while providing a seven-layer floor that can withstand everyday family use.


Our design team went the extra distance to create an accessible collection: a wide range of natural wood and stone effects in appealing shades ensures that Primero can be enjoyed in every style of home.

66

Developed and produced in Belgium, these affordable quality floors are made to endure every household.



mero 5



Why choose Primero?

BENEFITS OF PRIMERO

Soft, warm and quiet, Primero is a floor that makes everyone feel comfortable. What's more, its long-lasting finish is beautifully simple to look after.

Affordable quality

Made in Belgium, Primero's seven-layer construction is strong, stable and resistant to temperature changes. This means a floor that's ready for modern life.

Natural beauty

Primero finds inspiration in the beauty of wood and stone. Its minimal pattern repeat means every room enjoys a natural look.

Easy-going comfort

Choosing Primero means choosing a floor that's quickly installed and easy to maintain. Its soft underfoot feel, warmth and noise absorption make sure you enjoy a comfortable home.

For a better planet

Because it lasts, Primero is a great sustainable choice. With recycled content and low impact manufacturing in Belgium, this is a floor that takes its responsibility to the planet seriously.










Installation

VINYL CLICK & DRYBACK SYSTEM

Primero is remarkably easy to install. Available in either glue or click flavours, you can choose the method that's best for you. Stick down or lock together, Primero's world-class dimensional stability and high-strength compact layer deliver a lasting result.

CLICK DRYBACK





For detailed Click installation instructions, please check



For detailed **Dryback** installation instructions, please check www.installandclean.com/en/lvtdryback





Choose the correct underlay/adhesive Click Dryback Small temperature Big temperature Self-adhesive Adhesive fluctuations fluctuations underlay Big temperature Acoustics Acoustics fluctuations and/or important very important high temperatures Comfort Flex Pro Acoustic Pressure High underlay underlay Comfort Sensitive **Temperature** underlay Adhesive Adhesive

rimero

P



302 m2 24913




22858 204 m2




242 m2 22139











Navona Stone



46920 0 m2



46952 8 m2



46945 655 m²









Navona Stone 46920

Primero 31



Technical specifications

TECHNICAL INFO OF PRIMERO

		Dryback	Click	
PRODUCT INFORMATION				
Level of use	EN ISO 10874	23 - 31	23 - 31	
Total thickness	EN ISO 24346	2 mm	4.5 mm	
Wear layer	EN ISO 24340	0,3 mm	0,3 mm	
Wear Layer PUR treatment		Superguard Pro®	Superguard Pro®	
Total weight g/m²	EN ISO 23997	3328	7953	
SIZE & PACKING				
Planks	EN ISO 24342	16.3 x 98.8 cm	19.1 x 131.6 cm	
Tiles	EN ISO 24342	32.9 x 65.9 cm	32.4 x 65.5 cm	
Box planks		3.87 m² 24 pcs/box	1.76 m² 7 pcs/box	
Box tiles		3.90 m² 18 pcs/box	1.49 m² 7 pcs/box	
TEST RESULTS				
Inflammability	EN 13501	Bfl-S1		
Abrasion group	EN ISO 660-2	Class T		
Scratch resistance	EN 16094	≤MSR-A2, ≤MSR-B2		
Squareness	EN ISO 24342	≤ 0,20 mm		
Straightness	EN ISO 24342a	≤ 0,35 mm		
Slip resistance	EN 13893	DS		
Slip restraint	DIN 51130	R10		
Residual indentation	EN ISO 24343-1	2 0,10 mm		
Furniture leg resistance	EN ISO 16581	No cracks, no damage		
Curling	EN ISO 23999	<u> 1</u> 21mm	≤ l1lmm	
Dimensional stability	EN ISO 20326	Norm: ≤ 1 0,25 1 % Average result: ≤ 0,10%	Norm: £ 0,15 % Average result: £ 0,10%	
Thermal resistance R	EN 12667	0.04 m ² K/W	0.04 m² K/W	
Acoustic insulation	EN ISO 717-2	4 dB		
Acoustic insulation + Xtrafloor Acoustic Comfort		19 dB		
Castor chair resistance	EN ISO 4918	No damage to wearlayer, no delamination		
Stain resistance	EN ISO 26987	Very good		
Light fastness	EN ISO 105-B02	≥ 6		
Underfloor heating and cooling	EN 12524	Suitable, max 27°C		
Warranty (year)		12 Residential - 5 Commercial		













warranty covers manufacturing ects and premature wear in the event of normal use.



Primero

Meet IVC Group

IVC Group is a global player in the design and manufacturing of flooring solutions including Carpet Tiles, Luxury Vinyl Tiles (LVT), Heterogeneous Vinyl for use in business, public and private environments. Accountable for our actions, we design and make floors responsibly in Belgium, developing a circular approach to the future of flooring.

IVC Group is part of Mohawk Industries Inc., the world's largest flooring company. With 1,500 employees and 7 production sites in Europe and Russia, IVC Group produces over 130,000,000 m² of flooring every year.

Did you know...

that IVC Group employs over 30 different nationalities worldwide? That's the many cultures and inspirations which go into our eclectic floor designs, explaining their global appeal.







How we make our floors better for the environment?

At IVC Group, we truly believe in products that are developed with the future in mind. That's why we take the time to pause and reflect on the impacts of our entire strategy and operation, and we aim to contribute to the welfare of our planet and our people.





Read all about it in our sustainability whitepaper



